

## POE-63505IN

### Specification

<b>IEEE Standard</b>	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE802.3x Flow Control and Back Pressure, IEEE802.3af for POE IEEE802.3at for POE+
<b>Switch Architecture</b>	Back-plane (Switching Fabric): 1.0Gbps
<b>Data Processing</b>	Store and Forward
<b>Flow Control:</b>	IEEE 802.3x Flow Control and Back Pressure
<b>MAC address Table Size</b>	1K
<b>Packet Buffer Size</b>	1M
<b>Network Connector :</b>	4xRJ-45 10/100BaseT(X) auto negotiation, 4 10/100M POE+ 802.3at/af PSE port, 1 10/100M TX port Auto MDI/MDI-X function, Full/Half duplex
<b>Network Cable</b>	UTP/STP above Cat.5e Cable
	EIA/TIA-568 10-ohm (100m)
	Fiber Cable (Multi-mode):50/125um,62.5/125um Fiber Cable (Single-mode): 9/125um
<b>Protocol</b>	CSMA/CD
<b>LED</b>	PW1(Power 1) Green, PW2(Power 2) Green, PW3(Power DIN) Green SW( Relay) Amber,
	TX/RJ-45 port: Green --- LNK (Link/Active) Amber --- POE link
	FX Fiber port: (N/A)
<b>Reserve polarity protection</b>	Present
<b>Overload current protection</b>	Present
<b>Power Supply</b>	Redundant Dual DC 12V-56V Power Input, Switch input 12V-56VDC POE input 48-56VDC
<b>Power Consumption</b>	3.76W@48 VDC full load, Without POE
<b>Alarm Relay Contact</b>	Relay outputs with current carrying capacity of 1 A @24VDC, Relay in open circuit mode when 2 powers are

	connected. In short circuit mode when only one power supply is connected
<b>POE power</b>	Input Voltage 48VDC-56VDC. POE power per port 30watts. Maximum 36Watts with 56VDC input. Maximum total power 126Watts with 56VDC input
<b>Removable Terminal Block</b>	Provide 2 Redundant power , Alarm relay contact ,6 Pin Wire range: 0.34mm <sup>2</sup> to 2.5mm <sup>2</sup> Solid wire (AWG):12-24/14-22 Stranded wire(AWG): 12-24/14-22 Torque:5lb-In/0.5Nm/0.56Nm Wire Strip length: 7-8mm
<b>Operating Temperature</b>	-40°C to 75°C
<b>Operating Humidity</b>	5% to 95% (Non-condensing)
<b>Storage Temperature</b>	-40°C to 85°C
<b>MTBF (mean time between failure)</b>	510,304 hrs ( MIL-HDBK-217F) at 25°C
<b>Housing</b>	Rugged Metal ,IP30 Protection
<b>Case Dimension (LxWxD)</b>	142mmx37mmx105mm (LxWxD)
<b>Installation mounting</b>	DIN-Rail and wall mount brackets included
<b>Certificates:</b>	
<b>Safety</b>	IEC EN60950-1
<b>EMC/EMS</b>	CE, FCC, EN55032/24, VCCI
<b>EMI</b>	FCC Part 15 Subpart B Class A
<b>EN 60068-2-6</b>	Vibration
<b>EN 60068-2-27</b>	Shock
<b>EN 60068-2-32</b>	Free Fall