

Dyna-Switch/16 and 24

16/24 Port 10/100Base-TX Fast Ethernet Switches

PART NUMBER	DESCRIPTION
FEP-31016T-2	16 Port 10/100Base-TX Fast Ethernet Switch
FEP-31024T-2	24 Port 10/100Base-TX Fast Ethernet Switch

Specifications

Standards:

IEEE 802.3 10BASE-T Ethernet,
IEEE 802.3u 100BASE-TX Fast Ethernet
ANSI/IEEE standard 802.3 N-Way Auto-negotiation

Interface:

Sixteen (16) or Twenty-four (24) RJ-45 Jacks

Protocol:

CSMA/CD

Max Forwarding and Max Filtering Rate:

14,880 pps - Ethernet port, 148,800 pps - Fast Ethernet port

Buffer Memory:

1.25Mbits

MAC Address Table:

4K Entry

LED Indicators:

Per port: Link/Activity, Duplex Mode/Collision
Per unit: Power

Cable distance:

100m Max. with Category 3, 5e, 6 UTP for 10Base-T
100m Max. with Category 5e, 6 UTP for 100Base-TX

Dimensions:

17.31" x 4.75" x 1.75" (L x W x H)
440mm x 160mm x 44mm

Enclosure:

Metal

Operating Temperature:

0°C - 45°C (32°F - 113°F)

Operating Humidity:

10% - 90%, non-condensing

Power Supply:

100~240VAC, 50~60Hz, Internal universal power supply

EMI:

FCC Class A, CE Mark

Safety:

UL, cUL



908 Canada Court
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
Specifications subject to change without notice.